

What is claimed is:

1. A handle for opening and closing a shoji, comprising a pedestal fixed to the window frame side stile of a sliding door shoji or the lower rail of a raising-lowering shoji; a lever handle attached to this pedestal and swingably pivoted in a predetermined angle range; a kicking-out member fixed to a shaft portion of said lever handle and projected toward the window frame side by the swinging operation of said lever handle performed by opening and operating said sliding door shoji, and assisting the opening operation of the shoji by reaction force for kicking-out the window frame; and a spring member for biasing this kicking-out member toward a projection opposing side rotating direction.

2. The handle for opening and closing a shoji according to claim 1, wherein an auxiliary lock is constructed by arranging a rotatable locking hook piece in said lever handle, and fixing a receiving piece freely engaged with and disengaged from said locking hook piece to the window frame side.

3. The handle for opening and closing a shoji according to claim 1, wherein an auxiliary lock is constructed by arranging a rotatable locking hook piece on the window frame side, and forming a receiving engaging portion freely engaged with and disengaged from said locking hook piece in said lever handle.

4. The handle for opening and closing a shoji according to claim 1, wherein an auxiliary lock is constructed such that

a locking plate slidable in the vertical direction and having a locking hook portion projected to the exterior from a side edge of the rail is arranged in said pedestal portion, and a hole portion for locking freely engaged with and disengaged from said locking hook portion by the sliding operation of said locking plate is arranged on the window frame side.

5. The handle for opening and closing a shoji according to claim 1, wherein an auxiliary lock is constructed such that a locking plate swung by the swinging operation of said lever handle performed by opening and operating said sliding door shoji or said raising-lowering shoji, and having a locking hook portion projected to the exterior from a side edge of the rail is arranged in said pedestal portion, and a hole portion for locking freely engaged with and disengaged from said locking hook portion by the swinging operation of said locking plate is arranged on the window frame side.